



L480502630

LED PLC G24q 4 pin Glass T34x168mm
230V 9W 1280Lm 830 AC 3000K (repl.
PLDE26W) Opal Non-Dimmable

Marine & Industry, PLC G24q 4pin



General		Energy		
Eprel registration no	1869526	Operating voltage	230 V	
Socket	G24q	Volt	220..240 V	
Bulb shape	T34	Frequency	50..60 Hz	
Width	34.00 mm	Watt	9 W	
Depth	34.00 mm	Current type	AC	
Height	168.00 mm	Power factor	0.5	
Finish	Opal	Energy efficiency class	D	
Colour	White	Energy consumption	9 W	
Colour housing	White	Lamp efficacy	142.22	
Body material	Glass	LED		
Lifespan	30000 hours	Filament LED	No	
Switches	15000	LED type	SMD 2835	
Beam angle	270 °	Dimm type	Non-Dim	
Dimmable	No	Number of leds / sticks	72	
Degree of protection	IP20	Colour consistency SDCM	SDCM6	
Net weight	0.072 kg	Dim to warm	No	
Warranty	2 years	Adjustable beam angle	No	
Light		Ordering details		
Kelvin	3000 K	L480502630	Quantity pc(s)	EAN
Colour temp nr	830	Single package	1	8718739071957
Stable lumen	1280 lm	Inner carton	10	18718739071954
Color Rendering Index (CRI)	80	Outer carton	100	28718739071951

