



L480502640

LED PLC G24Q 4 pin Glass T34x168mm
230V 9W 1360Lm 840 AC 4000K (repl.
PLDE26W) Opal Non-Dimmable

Marine & Industry, Led PLC G24Q 4pin



General	
Eprel registration no	1869527
Socket	G24q
Bulb shape	T34
Width	34.00 mm
Depth	35.00 mm
Height	168.00 mm
Finish	Opal
Colour	White
Colour housing	White
Body material	Glass
Lifespan	25000 hours
Switches	15000
Beam angle	270 °
Dimmable	No
Degree of protection	IP20
Net weight	0.073 kg
Warranty	2 years

Energy	
Operating voltage	230 V
Volt	220..240 V
Frequency	50..60 Hz
Watt	9 W
Current type	AC
Power factor	0.5
Energy efficiency class	D
Energy consumption	9 W
Replacement wattage	91 W
Lamp efficacy	151.11

LED	
Filament LED	No
LED type	SMD 2835
Dimm type	Non-Dim
Number of leds / sticks	72
Colour consistency SDCM	SDCM6
Dim to warm	No
Adjustable beam angle	No

Light	
Kelvin	4000 K
Colour temp nr	840
Stable lumen	1360 lm
Color Rendering Index (CRI)	80

Ordering details		
L480502640	Quantity pc(s)	EAN
Single package	1	8718739071964
Inner carton	10	18718739071961
Outer carton	100	28718739071968