



## L480502665

LED PLC G24Q 4 pin Glass T34x163mm  
230V 9W 1360Lm 865 AC 6500K (repl.  
PLDE26W) Opal Non-Dimmable

### Marine & Industry, Led PLC G24Q 4pin



| General                     |             | Energy                  |                |                |
|-----------------------------|-------------|-------------------------|----------------|----------------|
| Eprel registration no       | 2039301     | Operating voltage       | 230 V          |                |
| Socket                      | G24q        | Volt                    | 220..240 V     |                |
| Bulb shape                  | T35         | Frequency               | 50..60 Hz      |                |
| Width                       | 34.00 mm    | Watt                    | 9 W            |                |
| Depth                       | 35.00 mm    | Current type            | AC             |                |
| Height                      | 163.00 mm   | Power factor            | 0.9            |                |
| Finish                      | Opal        | Energy efficiency class | D              |                |
| Colour                      | White       | Energy consumption      | 9 W            |                |
| Colour housing              | White       | Replacement wattage     | 91 W           |                |
| Body material               | Glass       | Lamp efficacy           | 151.11         |                |
| Lifespan                    | 25000 hours |                         |                |                |
| Switches                    | 15000       | LED                     |                |                |
| Beam angle                  | 270 °       | Filament LED            | No             |                |
| Dimmable                    | No          | LED type                | SMD 2835       |                |
| Degree of protection        | IP20        | Dimm type               | Non-Dim        |                |
| Net weight                  | 0.073 kg    | Number of leds / sticks | 72             |                |
| Warranty                    | 2 years     | Colour consistency SDCM | SDCM6          |                |
|                             |             | Dim to warm             | No             |                |
|                             |             | Adjustable beam angle   | No             |                |
| Light                       |             | Ordering details        |                |                |
| Kelvin                      | 6500 K      | L480502665              | Quantity pc(s) | EAN            |
| Colour temp nr              | 865         | Single package          | 1              | 8718739071971  |
| Stable lumen                | 1360 lm     | Inner carton            | 10             | 18718739071978 |
| Color Rendering Index (CRI) | 80          | Outer carton            | 100            | 28718739071975 |