



## L480502665

LED PLC G24Q 4 pin Glass T34x168mm  
230V 9W 1360Lm 865 AC 6500K (repl.  
PLDE26W) Opal Non-Dimmable

### Marine & Industry, Led PLC G24Q 4pin



General		Energy	
Epel registration no	2039301	Operating voltage	230 V
Socket	G24q	Volt	220..240 V
Bulb shape	T34	Frequency	50..60 Hz
Width	34.00 mm	Watt	9 W
Depth	35.00 mm	Current type	AC
Height	168.00 mm	Power factor	0.9
Finish	Opal	Energy efficiency class	D
Colour	White	Energy consumption	9 W
Colour housing	White	Replacement wattage	91 W
Body material	Glass	Lamp efficacy	151.11
Lifespan	25000 hours	LED	
Switches	15000	Filament LED	No
Beam angle	270 °	LED type	SMD 2835
Dimmable	No	Dimm type	Non-Dim
Degree of protection	IP20	Number of leds / sticks	72
Net weight	0.073 kg	Colour consistency SDCM	SDCM6
Warranty	2 years	Dim to warm	No
		Adjustable beam angle	No
Light		Ordering details	
Kelvin	6500 K	L480502665	Quantity pc(s) EAN
Colour temp nr	865	Single package	1 8718739071971
Stable lumen	1360 lm	Inner carton	10 18718739071978
Color Rendering Index (CRI)	80	Outer carton	100 28718739071975