

L480603230

LED PLT GX24q 4 pin Glass T45x146mm
230V 10W 1350Lm 830 AC 3000K (repl.
PLTE32W) Opal Non-Dimmable

Marine & Industry, Led PLT GX24q 4pin



General	
Eprel registration no	2039302
Socket	GX24q
Bulb shape	T45
Width	45.00 mm
Depth	49.50 mm
Height	146.00 mm
Finish	Opal
Colour	White
Colour housing	White
Body material	Glass
Lifespan	25000 hours
Switches	15000
Beam angle	270 °
Dimmable	No
Degree of protection	IP20
Net weight	0.099 kg
Warranty	2 years

Energy	
Operating voltage	230 V
Volt	220..240 V
Frequency	50..60 Hz
Watt	10 W
Current type	AC
Power factor	0.9
Energy efficiency class	D
Energy consumption	10 W
Replacement wattage	91 W
Lamp efficacy	135.00

LED	
Filament LED	No
LED type	SMD 2835
Dimm type	Non-Dim
Number of leds / sticks	72
Colour consistency SDCM	SDCM6
Dim to warm	No
Adjustable beam angle	No

Light	
Kelvin	3000 K
Colour temp nr	830
Stable lumen	1350 lm
Color Rendering Index (CRI)	80

Ordering details		
L480603230	Quantity pc(s)	EAN
Single package	1	8718739072008
Inner carton	10	18718739072005
Outer carton	100	28718739072002