



## L480603240

LED PLT GX24q 4 pin Glass T45x146mm  
230V 10W 1450Lm 840 AC 4000K (repl.  
PLTE32W) Opal Non-Dimmable

### Marine & Industry, Led PLT GX24q 4pin



| General               |             |
|-----------------------|-------------|
| Eprel registration no | 2039303     |
| Socket                | GX24q       |
| Bulb shape            | T45         |
| Width                 | 45.00 mm    |
| Depth                 | 49.50 mm    |
| Height                | 146.00 mm   |
| Finish                | Opal        |
| Colour                | White       |
| Colour housing        | White       |
| Body material         | Glass       |
| Lifespan              | 25000 hours |
| Switches              | 15000       |
| Beam angle            | 270 °       |
| Dimmable              | No          |
| Degree of protection  | IP20        |
| Net weight            | 0.099 kg    |
| Warranty              | 2 years     |

| Energy                  |                |                |
|-------------------------|----------------|----------------|
| Operating voltage       | 230 V          |                |
| Volt                    | 220..240 V     |                |
| Frequency               | 50..60 Hz      |                |
| Watt                    | 10 W           |                |
| Current type            | AC             |                |
| Power factor            | 0.9            |                |
| Energy efficiency class | D              |                |
| Energy consumption      | 10 W           |                |
| Replacement wattage     | 96 W           |                |
| Lamp efficacy           | 145.00         |                |
| LED                     |                |                |
| Filament LED            | No             |                |
| LED type                | SMD 2835       |                |
| Dimm type               | Non-Dim        |                |
| Number of leds / sticks | 72             |                |
| Colour consistency SDCM | SDCM6          |                |
| Dim to warm             | No             |                |
| Adjustable beam angle   | No             |                |
| Ordering details        |                |                |
| L480603240              | Quantity pc(s) | EAN            |
| Single package          | 1              | 8718739072015  |
| Inner carton            | 10             | 18718739072012 |
| Outer carton            | 100            | 28718739072019 |

| Light                       |         |
|-----------------------------|---------|
| Kelvin                      | 4000 K  |
| Colour temp nr              | 840     |
| Stable lumen                | 1450 lm |
| Color Rendering Index (CRI) | 80      |