



## L480603265

LED PLT GX24q 4 pin Glass T45x146mm  
230V 10W 1450Lm 865 AC 6500K (repl.  
PLTE32W) Opal Non-Dimmable

### Marine & Industry, Led PLT GX24q 4pin



General	
Epel registration no	2039305
Socket	GX24q
Bulb shape	T45
Width	45.00 mm
Depth	49.50 mm
Height	146.00 mm
Finish	Opal
Colour	White
Colour housing	White
Body material	Glass
Lifespan	25000 hours
Switches	15000
Beam angle	270 °
Dimmable	No
Degree of protection	IP20
Net weight	0.099 kg
Warranty	2 years

Energy		
Operating voltage	230 V	
Volt	220..240 V	
Frequency	50..60 Hz	
Watt	10 W	
Current type	AC	
Power factor	0.9	
Energy efficiency class	D	
Energy consumption	10 W	
Replacement wattage	96 W	
Lamp efficacy	145.00	
LED		
Filament LED	No	
LED type	SMD 2835	
Dimm type	Non-Dim	
Number of leds / sticks	72	
Colour consistency SDCM	SDCM6	
Dim to warm	No	
Adjustable beam angle	No	
Ordering details		
L480603265	Quantity pc(s)	EAN
Single package	1	8718739072022
Inner carton	10	18718739072029
Outer carton	100	28718739072026

Light	
Kelvin	6500 K
Colour temp nr	865
Stable lumen	1450 lm
Color Rendering Index (CRI)	80