



L480604230

LED PLT GX24q 4 pin Glass T49x165mm
230V 13W 1750Lm 830 AC 3000K (repl.
PLTE42W) Opal Non-Dimmable

Marine & Industry, PLT GX24q 4pin



| General | | Energy | | |
|-----------------------------|-------------|-------------------------|----------------|----------------|
| Eprel registration no | 1869528 | Operating voltage | 230 V | |
| Socket | GX24q | Volt | 220..240 V | |
| Bulb shape | T49 | Frequency | 50..60 Hz | |
| Width | 49.00 mm | Watt | 13 W | |
| Depth | 45.00 mm | Current type | AC | |
| Height | 165.00 mm | Power factor | 0.5 | |
| Finish | Opal | Energy efficiency class | E | |
| Colour | White | Energy consumption | 13 W | |
| Colour housing | White | Lamp efficacy | 134.62 | |
| Body material | Glass | LED | | |
| Lifespan | 30000 hours | Filament LED | No | |
| Switches | 15000 | LED type | SMD 2835 | |
| Beam angle | 270 ° | Dimm type | Non-Dim | |
| Dimmable | No | Number of leds / sticks | 108 | |
| Degree of protection | IP20 | Colour consistency SDCM | SDCM6 | |
| Net weight | 0.110 kg | Dim to warm | No | |
| Warranty | 2 years | Adjustable beam angle | No | |
| Light | | Ordering details | | |
| Kelvin | 3000 K | L480604230 | Quantity pc(s) | EAN |
| Colour temp nr | 830 | Single package | 1 | 8718739072039 |
| Stable lumen | 1750 lm | Inner carton | 10 | 18718739072036 |
| Color Rendering Index (CRI) | 80 | Outer carton | 100 | 28718739072033 |

