PROFESSIONAL LIGHTING

L480604230

LED PLT GX24q 4 pin Glass T49x165mm 230V 13W 1750Lm 830 AC 3000K (repl. PLTE42W) Opal Non-Dimmable

Marine & Industry, PLT GX24q 4pin AC





General	
Eprel registration no	1869528
Socket	GX24q
Bulb shape	T49
Width	49.00 mm
Depth	45.00 mm
Height	165.00 mm
Finish	Opal
Colour	White
Colour housing	White
Body material	Glass
Lifespan	30000 hours
Switches	15000
Beam angle	270 °
Dimmable	No
Degree of protection	IP20
Net weight	0.110 kg
Warranty	2 years

Energy	
Operating voltage	230 V
Volt	220..240 V
Frequency	50..60 Hz
Watt	13 W
Current type	AC
Power factor	0.5
Energy efficiency class	E
Energy consumption	13 W
Lamp efficacy	134.62

LED	
Filament LED	No
LED type	SMD 2835
Dimm type	Non-Dim
Number of leds / sticks	108
Colour consistency SDCM	SDCM6
Dim to warm	No
Adjustable beam angle	No

Light	
CRI	80
Kelvin	3000 K
Colour temp nr	830
Stable lumen	1750 lm

Ordering details		
L480604230	Quantity pc(s)	EAN
Single package	1	8718739072039
Inner carton	10	18718739072036
Outer carton	100	28718739072033

CE | UK CA

Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | www.spl-lighting.com | info@spl-lighting.com | Telephone +31 (0)76 - 503 77 17
Fax +31 (0)76 501 78 69 | splprofessionallighting | schiefersignaal