



## L480604240

LED PLT GX24q 4 pin Glass T49x165mm  
230V 13W 1890Lm 840 AC 4000K (repl.  
PLTE42W) Opal Non-Dimmable

### Marine & Industry, PLT GX24q 4pin



General		Energy		
Eprel registration no	1869529	Operating voltage	230 V	
Socket	GX24q	Volt	220..240 V	
Bulb shape	T49	Frequency	50..60 Hz	
Width	49.00 mm	Watt	13 W	
Depth	45.00 mm	Current type	AC	
Height	165.00 mm	Power factor	0.5	
Finish	Opal	Energy efficiency class	D	
Colour	White	Energy consumption	13 W	
Colour housing	White	Lamp efficacy	145.38	
Body material	Glass	<b>LED</b>		
Lifespan	25000 hours	Filament LED	No	
Switches	15000	LED type	SMD 2835	
Beam angle	270 °	Dimm type	Non-Dim	
Dimmable	No	Number of leds / sticks	108	
Degree of protection	IP20	Colour consistency SDCM	SDCM6	
Net weight	0.110 kg	Dim to warm	No	
Warranty	2 years	Adjustable beam angle	No	
<b>Light</b>		<b>Ordering details</b>		
Kelvin	4000 K	L480604240	Quantity pc(s)	EAN
Colour temp nr	840	Single package	1	8718739072046
Stable lumen	1890 lm	Inner carton	10	18718739072043
Color Rendering Index (CRI)	80	Outer carton	100	28718739072040

