



## L480604265

LED PLT GX24q 4 pin Glass T45x167mm  
230V 13W 1890Lm 865 AC 6500K (repl.  
PLTE42W) Opal Non-Dimmable

### Marine & Industry, Led PLT GX24q 4pin



General	
Eprel registration no	2039308
Socket	GX24q
Bulb shape	T45
Width	45.00 mm
Depth	49.50 mm
Height	167.00 mm
Finish	Opal
Colour	White
Colour housing	White
Body material	Glass
Lifespan	25000 hours
Switches	15000
Beam angle	270 °
Dimmable	No
Degree of protection	IP20
Net weight	0.114 kg
Warranty	2 years

Energy	
Operating voltage	230 V
Volt	220..240 V
Frequency	50..60 Hz
Watt	13 W
Current type	AC
Power factor	0.9
Energy efficiency class	D
Energy consumption	13 W
Replacement wattage	120 W
Lamp efficacy	145.38

LED	
Filament LED	No
LED type	SMD 2835
Dimm type	Non-Dim
Number of leds / sticks	108
Colour consistency SDCM	SDCM6
Dim to warm	No
Adjustable beam angle	No

Light	
Kelvin	6500 K
Colour temp nr	865
Stable lumen	1890 lm
Color Rendering Index (CRI)	80

Ordering details		
L480604265	Quantity pc(s)	EAN
Single package	1	8718739072053
Inner carton	10	18718739072050
Outer carton	100	28718739072057