PROFESSIONAL LIGHTING

L490112830-1

LED G13 Glass T8 Tube T26x1213mm
including pins 230V 2560Lm 16W 3000K
830 190° AC+CCG Milky Non-Dimmable

Marine & Industry, T8 Tube

General	
Eprel registration no	2433317
Socket	G13
Bulb shape	T8
Width	26.00 mm
Depth	26.00 mm
Height	1213.00 mm
Finish	Opal
Colour	White
Colour housing	White
Body material	Glass
Lifespan	25000 hours
Switches	50000
Beam angle	190 °
Dimmable	No
Degree of protection	IP20
Net weight	0.164 kg
Warranty	2 years

Energy	
Operating voltage	230 V
Volt	220..240 V
Frequency	50..60 Hz
Watt	16 W
Current type	AC
Power factor	0.5
Energy efficiency class	C
Energy consumption	16 W
Lamp efficacy	160.00

LED	
Filament LED	No
LED type	SMD 2835
Dimm type	Non-Dim
Number of leds / sticks	100
Colour consistency SDCM	SDCM5
Dim to warm	No
Adjustable beam angle	No

Light	
Kelvin	3000 K
Colour temp nr	830
Stable lumen	2560 lm
Color Rendering Index (CRI)	80

Ordering details		
L490112830-1	Quantity pc(s)	EAN
Single package	1	8718739082700
Outer carton	20	28718739082704

Remark

Can be quickly fitted as a replacement into luminaires operating on electro-magnetic control gear using the dummy starter, or AC 230V mains voltage with a simple re-wire (no dummy starter needed).

CE | UK CA

Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | www.spl-lighting.com | info@spl-lighting.com | Telephone +31 (0)76 - 503 77 17
Fax +31 (0)76 501 78 69 | splprofessionallighting | schiefersignaal