

L490112840-1

LED G13 Glass T8 Tube T26x1213mm
including pins 230V 2560Lm 16W 4000K
840 190° AC+CCG Milky Non-Dimmable

Marine & Industry, T8 Tube


General		Energy	
Eprel registration no	2433320	Operating voltage	230 V
Socket	G13	Volt	220..240 V
Bulb shape	T8	Frequency	50..60 Hz
Width	26.00 mm	Watt	16 W
Depth	26.00 mm	Current type	AC
Height	1213.00 mm	Power factor	0.5
Finish	Opal	Energy efficiency class	C
Colour	White	Energy consumption	16 W
Colour housing	White	Lamp efficacy	160.00
Body material	Glass	LED	
Lifespan	25000 hours	Filament LED	No
Switches	50000	LED type	SMD 2835
Beam angle	190 °	Dimm type	Non-Dim
Dimmable	No	Number of leds / sticks	100
Degree of protection	IP20	Colour consistency SDCM	SDCM5
Net weight	0.164 kg	Dim to warm	No
Warranty	2 years	Adjustable beam angle	No

Light		Ordering details		
Kelvin	4000 K	L490112840-1	Quantity pc(s)	EAN
Colour temp nr	840	Single package	1	8718739082717
Stable lumen	2560 lm	Outer carton	20	28718739082711
Color Rendering Index (CRI)	80			

Remark
Can be quickly fitted as a replacement into luminaires operating on electro-magnetic control gear using the dummy starter, or AC 230V mains voltage with a simple re-wire (no dummy starter needed).