

L490112865

LED G13 Glass T8 Tube T26x1213mm
including pins 230V 2560Lm 16W 6500K
865 190° AC+CCG Milky Non-Dimmable

Marine & Industry, T8 Tube


| General | | Energy | |
|-----------------------|-------------|-------------------------|------------|
| Eprel registration no | 2433321 | Operating voltage | 230 V |
| Socket | G13 | Volt | 220..240 V |
| Bulb shape | T8 | Frequency | 50..60 Hz |
| Width | 26.00 mm | Watt | 16 W |
| Depth | 26.00 mm | Current type | AC |
| Height | 1213.00 mm | Power factor | 0.5 |
| Finish | Opal | Energy efficiency class | C |
| Colour | White | Energy consumption | 16 W |
| Colour housing | White | Lamp efficacy | 160.00 |
| Body material | Glass | LED | |
| Lifespan | 25000 hours | Filament LED | No |
| Switches | 50000 | LED type | SMD 2835 |
| Beam angle | 190 ° | Dimm type | Non-Dim |
| Dimmable | No | Number of leds / sticks | 100 |
| Degree of protection | IP20 | Colour consistency SDCM | SDCM5 |
| Net weight | 0.164 kg | Dim to warm | No |
| Warranty | 2 years | Adjustable beam angle | No |

| Light | |
|-----------------------------|---------|
| Kelvin | 6500 K |
| Colour temp nr | 865 |
| Stable lumen | 2560 lm |
| Color Rendering Index (CRI) | 80 |

| Remark |
|---|
| Can be quickly fitted as a replacement into luminaires operating on electro-magnetic control gear using the dummy starter, or on electronic gear with a simple re-wire (no dummy starter needed). |

| Ordering details | | |
|------------------|----------------|----------------|
| L490112865 | Quantity pc(s) | EAN |
| Single package | 1 | 8718739082755 |
| Outer carton | 20 | 28718739082759 |