

L490115830-1

LED G13 Glass T8 Tube T26x1514mm
including pins 230V 3200Lm 20W 3000K
830 190° AC+CCG Milky Non-Dimmable

Marine & Industry, T8 Tube


General		Energy	
Eprel registration no	2433322	Operating voltage	230 V
Socket	G13	Volt	220..240 V
Bulb shape	T8	Frequency	50..60 Hz
Width	26.00 mm	Watt	20 W
Depth	26.00 mm	Current type	AC
Height	1514.00 mm	Power factor	0.5
Finish	Opal	Energy efficiency class	C
Colour	White	Energy consumption	20 W
Colour housing	White	Lamp efficacy	160.00
Body material	Glass	LED	
Lifespan	25000 hours	Filament LED	No
Switches	50000	LED type	SMD 2835
Beam angle	190 °	Dimm type	Non-Dim
Dimmable	No	Number of leds / sticks	120
Degree of protection	IP20	Colour consistency SDCM	SDCM5
Net weight	0.200 kg	Dim to warm	No
Warranty	2 years	Adjustable beam angle	No

Light	
Kelvin	3000 K
Colour temp nr	830
Stable lumen	3200 lm
Color Rendering Index (CRI)	80

Remark
Can be quickly fitted as a replacement into luminaires operating on electro-magnetic control gear using the dummy starter, or on electronic gear with a simple re-wire (no dummy starter needed).

Ordering details		
L490115830-1	Quantity pc(s)	EAN
Single package	1	8718739082724
Outer carton	20	28718739082728