PROFESSIONAL LIGHTING

L490115840-1

LED G13 Glass T8 Tube T26x1514mm
including pins 230V 3200Lm 20W 4000K
840 190° AC+CCG Milky Non-Dimmable



Marine & Industry, T8 Tube AC+CCG

General	
Eprel registration no	2433324
Socket	G13
Bulb shape	T8
Width	26.00 mm
Depth	26.00 mm
Height	1514.00 mm
Finish	Opal
Colour	White
Colour housing	White
Body material	Glass
Lifespan	25000 hours
Switches	50000
Beam angle	190 °
Dimmable	No
Degree of protection	IP20
Net weight	0.200 kg
Warranty	2 years

Energy	
Operating voltage	230 V
Volt	220..240 V
Frequency	50..60 Hz
Watt	20 W
Current type	AC
Power factor	0.5
Energy efficiency class	C
Energy consumption	20 W
Lamp efficacy	160.00

LED	
Filament LED	No
LED type	SMD 2835
Dimm type	Non-Dim
Number of leds / sticks	120
Colour consistency SDCM	SDCM5
Dim to warm	No
Adjustable beam angle	No

Light	
CRI	80
Kelvin	4000 K
Colour temp nr	840
Stable lumen	3200 lm

Ordering details		
L490115840-1	Quantity pc(s)	EAN
Single package	1	8718739082731
Outer carton	20	28718739082735

Remark
Can be quickly fitted as a replacement into luminaires operating on electro-magnetic control gear using the dummy starter, or AC 230V mains voltage with a simple re-wire (no dummy starter needed).

CE | UK CA

Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | www.spl-lighting.com | info@spl-lighting.com | Telephone +31 (0)76 - 503 77 17
Fax +31 (0)76 501 78 69 | splprofessionallighting | schiefersignaal