



## L490115840

LED G13 Glass T8 Tube T26x1514mm  
including pin 230V 2750Lm 21W 4000K  
840 210° AC+CCG Milky Non-Dimmable

### Marine & Industry, T8 Tube



General		Energy	
Epel registration no	831495	Operating voltage	230 V
Socket	G13	Volt	220..240 V
Bulb shape	T8	Frequency	50..60 Hz
Width	1514.00 mm	Watt	21 W
Depth	26.00 mm	Current type	AC
Height	26.00 mm	Power factor	0.9
Finish	Opal	Energy efficiency class	E
Colour	White	Energy consumption	21 W
Colour housing	White	Replacement wattage	165 W
Body material	Glass	Lamp efficacy	130.95
Lifespan	50000 hours	<b>LED</b>	
Switches	25000		
Beam angle	210 °		
Dimmable	No		
Degree of protection	IP20		
Net weight	0.265 kg		
Warranty	2 years		
<b>Light</b>		Filament LED	No
		LED type	SMD 2835
		Dimm type	Non-Dim
		Number of leds / sticks	88
		Colour consistency SDCM	SDCM5
		Dim to warm	No
		Adjustable beam angle	No

Light		Ordering details		
Kelvin	4000 K	L490115840	Quantity pc(s)	EAN
Colour temp nr	840	Single package	1	8718739061705
Stable lumen	2750 lm	Outer carton	10	28718739061709
Color Rendering Index (CRI)	80			

### Remark

Can be quickly fitted as a replacement into luminaires operating on electro-magnetic control gear using the dummy starter, or on electronic gear with a simple re-wire (no dummy starter needed).

