



## L490115840

LED G13 Glass T8 Tube T26x1514mm  
including pin 230V 2750Lm 21W 4000K  
840 210° AC+CCG Milky Non-Dimmable

### Marine & Industry, T8 Tube



| General              |             | Energy                  |                |
|----------------------|-------------|-------------------------|----------------|
| Epel registration no | 831495      | Operating voltage       | 230 V          |
| Socket               | G13         | Volt                    | 220..240 V     |
| Bulb shape           | T8          | Frequency               | 50..60 Hz      |
| Width                | 1514.00 mm  | Watt                    | 21 W           |
| Depth                | 26.00 mm    | Current type            | AC             |
| Height               | 26.00 mm    | Power factor            | 0.9            |
| Finish               | Opal        | Energy efficiency class | E              |
| Colour               | White       | Energy consumption      | 21 W           |
| Colour housing       | White       | Replacement wattage     | 165 W          |
| Body material        | Glass       | Lamp efficacy           | 130.95         |
| Lifespan             | 50000 hours | LED                     |                |
| Switches             | 25000       |                         |                |
| Beam angle           | 210 °       |                         |                |
| Dimmable             | No          |                         |                |
| Degree of protection | IP20        |                         |                |
| Net weight           | 0.265 kg    |                         |                |
| Warranty             | 2 years     |                         |                |
| Light                |             | Filament LED            | No             |
|                      |             | LED type                | SMD 2835       |
|                      |             | Dimm type               | Non-Dim        |
|                      |             | Number of leds / sticks | 88             |
|                      |             | Colour consistency SDCM | SDCM5          |
|                      |             | Dim to warm             | No             |
|                      |             | Adjustable beam angle   | No             |
| Ordering details     |             | L490115840              | Quantity pc(s) |
|                      |             | Single package          | 1              |
|                      |             | Outer carton            | 10             |
|                      |             |                         |                |

### Light

|                             |         |
|-----------------------------|---------|
| Kelvin                      | 4000 K  |
| Colour temp nr              | 840     |
| Stable lumen                | 2750 lm |
| Color Rendering Index (CRI) | 80      |

### Remark

Can be quickly fitted as a replacement into luminaires operating on electro-magnetic control gear using the dummy starter, or on electronic gear with a simple re-wire (no dummy starter needed).

