PROFESSIONAL LIGHTING

L490160830-1

LED G13 Glass T8 Tube T26x604mm including pins 230V 1280Lm 8W 3000K 830 190° AC+CCG Milky Non-Dimmable



Marine & Industry, T8 Tube AC+CCG

General	
Eprel registration no	2433326
Socket	G13
Bulb shape	T8
Width	26.00 mm
Depth	26.00 mm
Height	604.00 mm
Finish	Opal
Colour	White
Colour housing	White
Body material	Glass
Lifespan	25000 hours
Switches	50000
Beam angle	190 °
Dimmable	No
Degree of protection	IP20
Net weight	0.093 kg
Warranty	2 years

Energy	
Operating voltage	230 V
Volt	220..240 V
Frequency	50..60 Hz
Watt	8 W
Current type	AC
Power factor	0.5
Energy efficiency class	C
Energy consumption	8 W
Lamp efficacy	160.00

LED	
Filament LED	No
LED type	SMD 2835
Dimm type	Non-Dim
Number of leds / sticks	50
Colour consistency SDCM	SDCM5
Dim to warm	No
Adjustable beam angle	No

Light	
CRI	80
Kelvin	3000 K
Colour temp nr	830
Stable lumen	1280 lm

Ordering details		
L490160830-1	Quantity pc(s)	EAN
Single package	1	8718739082571
Outer carton	20	28718739082575

Remark
Can be quickly fitted as a replacement into luminaires operating on electro-magnetic control gear using the dummy starter, or AC 230V mains voltage with a simple re-wire (no dummy starter needed).

CE | UK CA

Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | www.spl-lighting.com | info@spl-lighting.com | Telephone +31 (0)76 - 503 77 17
Fax +31 (0)76 501 78 69 | splprofessionallighting | schiefersignaal