



L490160830

LED G13 Glass T8 Tube T26x604mm
including pin 230V 1000Lm 8W 3000K 830
210° AC+CCG Milky Non-Dimmable

Marine & Industry, T8 Tube



| General | | Energy | |
|-----------------------------|-------------|-------------------------|--------------------|
| Epel registration no | 831498 | Operating voltage | 230 V |
| Socket | G13 | Volt | 220..240 V |
| Bulb shape | T8 | Frequency | 50..60 Hz |
| Width | 26.00 mm | Watt | 8 W |
| Depth | 26.00 mm | Current type | AC |
| Height | 604.00 mm | Power factor | 0.9 |
| Finish | Opal | Energy efficiency class | E |
| Colour | White | Energy consumption | 8 W |
| Colour housing | White | Replacement wattage | 72 W |
| Body material | Glass | Lamp efficacy | 125.00 |
| Lifespan | 50000 hours | LED | |
| Switches | 25000 | Filament LED | No |
| Beam angle | 210 ° | LED type | SMD 2835 |
| Dimmable | No | Dimm type | Non-Dim |
| Degree of protection | IP20 | Number of leds / sticks | 40 |
| Net weight | 0.115 kg | Colour consistency SDCM | SDCM5 |
| Warranty | 2 years | Dim to warm | No |
| Light | | Adjustable beam angle | No |
| Kelvin | 3000 K | Ordering details | |
| Colour temp nr | 830 | L490160830 | Quantity pc(s) EAN |
| Stable lumen | 1000 lm | Single package | 1 8718739059122 |
| Color Rendering Index (CRI) | 80 | Outer carton | 25 28718739059126 |

Remark

Can be quickly fitted as a replacement into luminaires operating on electro-magnetic control gear using the dummy starter, or on electronic gear with a simple re-wire (no dummy starter needed).