



L490160840

LED G13 Glass T8 Tube T26x604mm
including pin 230V 1050Lm 8W 4000K 840
210° AC+CCG Milky Non-Dimmable

Marine & Industry, T8 Tube



General		Energy																							
Eprel registration no	831499	Operating voltage	230 V																						
Socket	G13	Volt	220..240 V																						
Bulb shape	T8	Frequency	50..60 Hz																						
Width	26.00 mm	Watt	8 W																						
Depth	26.00 mm	Current type	AC																						
Height	604.00 mm	Power factor	0.9																						
Finish	Opal	Energy efficiency class	E																						
Colour	White	Energy consumption	8 W																						
Colour housing	White	Replacement wattage	75 W																						
Body material	Glass	Lamp efficacy	131.25																						
Lifespan	50000 hours	<div>LED</div> <table><tr><td>Filament LED</td><td colspan="2">No</td></tr><tr><td>LED type</td><td colspan="2">SMD 2835</td></tr><tr><td>Dimm type</td><td colspan="2">Non-Dim</td></tr><tr><td>Number of leds / sticks</td><td colspan="2">40</td></tr><tr><td>Colour consistency SDCM</td><td colspan="2">SDCM5</td></tr><tr><td>Dim to warm</td><td colspan="2">No</td></tr><tr><td>Adjustable beam angle</td><td colspan="2">No</td></tr></table>			Filament LED	No		LED type	SMD 2835		Dimm type	Non-Dim		Number of leds / sticks	40		Colour consistency SDCM	SDCM5		Dim to warm	No		Adjustable beam angle	No	
Filament LED	No																								
LED type	SMD 2835																								
Dimm type	Non-Dim																								
Number of leds / sticks	40																								
Colour consistency SDCM	SDCM5																								
Dim to warm	No																								
Adjustable beam angle	No																								
Switches	25000																								
Beam angle	210 °																								
Dimmable	No																								
Degree of protection	IP20																								
Net weight	0.115 kg																								
Warranty	2 years																								
Light		Ordering details																							
Kelvin	4000 K	L490160840	Quantity pc(s)	EAN																					
Colour temp nr	840	Single package	1	8718739061668																					
Stable lumen	1050 lm	Outer carton	25	28718739061662																					
Color Rendering Index (CRI)	80																								

Remark

Can be quickly fitted as a replacement into luminaires operating on electro-magnetic control gear using the dummy starter, or on electronic gear with a simple re-wire (no dummy starter needed).

