



L490212830

LED G13 Glass T8 Tube T26x1213mm
including pin 230V 2800Lm 18W 3000K
830 210° AC+CCG Milky Non-Dimmable

Marine & Industry, T8 Tube Premium



General		Energy	
Eprel registration no	831502	Operating voltage	230 V
Socket	G13	Volt	220..240 V
Bulb shape	T8	Frequency	50..60 Hz
Width	26.00 mm	Watt	18 W
Depth	26.00 mm	Current type	AC
Height	1213.00 mm	Power factor	0.9
Finish	Opal	Energy efficiency class	D
Colour	White	Energy consumption	18 W
Colour housing	White	Lamp efficacy	155.56
Body material	Glass	LED	
Lifespan	50000 hours	Filament LED	No
Switches	25000	LED type	SMD 2835
Beam angle	210 °	Dimm type	Non-Dim
Dimmable	No	Number of leds / sticks	140
Degree of protection	IP20	Colour consistency SDCM	SDCM5
Net weight	0.208 kg	Dim to warm	No
Warranty	2 years	Adjustable beam angle	No

Light	
Kelvin	3000 K
Colour temp nr	830
Stable lumen	2800 lm
Color Rendering Index (CRI)	80

Remark
Can be quickly fitted as a replacement into luminaires operating on electro-magnetic control gear using the dummy starter, or on electronic gear with a simple re-wire (no dummy starter needed).

Ordering details		
L490212830	Quantity pc(s)	EAN
Single package	1	8718739061736
Outer carton	25	28718739061730

