



## L490212840

LED G13 Glass T8 Tube T26x1213mm  
including pin 230V 3000Lm 18W 4000K  
840 210° AC+CCG Milky Non-Dimmable

### Marine & Industry, T8 Tube Premium



General		Energy	
Eprel registration no	831504	Operating voltage	230 V
Socket	G13	Volt	220..240 V
Bulb shape	T8	Frequency	50..60 Hz
Width	26.00 mm	Watt	18 W
Depth	26.00 mm	Current type	AC
Height	1213.00 mm	Power factor	0.9
Finish	Opal	Energy efficiency class	C
Colour	White	Energy consumption	18 W
Colour housing	White	Lamp efficacy	166.67
Body material	Glass	<b>LED</b>	
Lifespan	50000 hours	Filament LED	No
Switches	25000	LED type	SMD 2835
Beam angle	210 °	Dimm type	Non-Dim
Dimmable	No	Number of leds / sticks	140
Degree of protection	IP20	Colour consistency SDCM	SDCM5
Net weight	0.204 kg	Dim to warm	No
Warranty	2 years	Adjustable beam angle	No

Light	
Kelvin	4000 K
Colour temp nr	840
Stable lumen	3000 lm
Color Rendering Index (CRI)	80

Remark
Can be quickly fitted as a replacement into luminaires operating on electro-magnetic control gear using the dummy starter, or AC 230V mains voltage with a simple re-wire (no dummy starter needed).

Ordering details		
L490212840	Quantity pc(s)	EAN
Single package	1	8718739061743
Outer carton	25	28718739061747

