



## L490215830

LED G13 Glass T8 Tube T26x1514mm  
including pin 230V 3700Lm 24W 3000K  
830 210° AC+CCG Milky Non-Dimmable

### Marine & Industry, T8 Tube Premium



General		Energy	
Epel registration no	831506	Operating voltage	230 V
Socket	G13	Volt	220..240 V
Bulb shape	T8	Frequency	50..60 Hz
Width	26.00 mm	Watt	24 W
Depth	26.00 mm	Current type	AC
Height	1514.00 mm	Power factor	0.9
Finish	Opal	Energy efficiency class	D
Colour	White	Energy consumption	24 W
Colour housing	White	Replacement wattage	197 W
Body material	Glass	Lamp efficacy	154.17
Lifespan	50000 hours	LED	
Switches	25000	Filament LED	No
Beam angle	210 °	LED type	SMD 2835
Dimmable	No	Dimm type	Non-Dim
Degree of protection	IP20	Number of leds / sticks	180
Net weight	0.242 kg	Colour consistency SDCM	SDCM5
Warranty	2 years	Dim to warm	No
Light		Adjustable beam angle	No
Kelvin	3000 K	Ordering details	
Colour temp nr	830	L490215830	Quantity pc(s) EAN
Stable lumen	3700 lm	Single package	1 8718739061750
Color Rendering Index (CRI)	80	Outer carton	25 28718739061754

### Remark

Can be quickly fitted as a replacement into luminaires operating on electro-magnetic control gear using the dummy starter, or on electronic gear with a simple re-wire (no dummy starter needed).

