

## L490215840

LED G13 Glass T8 Tube T26x1514mm  
including pin 230V 4000Lm 24W 4000K  
840 210° AC+CCG Milky Non-Dimmable

### Marine & Industry, T8 Tube Premium



| General               |             |
|-----------------------|-------------|
| Eprel registration no | 831507      |
| Socket                | G13         |
| Bulb shape            | T8          |
| Width                 | 26.00 mm    |
| Depth                 | 26.00 mm    |
| Height                | 1514.00 mm  |
| Finish                | Opal        |
| Colour                | White       |
| Colour housing        | White       |
| Body material         | Glass       |
| Lifespan              | 50000 hours |
| Switches              | 25000       |
| Beam angle            | 210 °       |
| Dimmable              | No          |
| Degree of protection  | IP20        |
| Net weight            | 0.265 kg    |
| Warranty              | 2 years     |

| Energy                  |            |
|-------------------------|------------|
| Operating voltage       | 230 V      |
| Volt                    | 220..240 V |
| Frequency               | 50..60 Hz  |
| Watt                    | 24 W       |
| Current type            | AC         |
| Power factor            | 0.9        |
| Energy efficiency class | C          |
| Energy consumption      | 24 W       |
| Replacement wattage     | 58 W       |
| Lamp efficacy           | 166.67     |

| LED                     |          |
|-------------------------|----------|
| Filament LED            | No       |
| LED type                | SMD 2835 |
| Dimm type               | Non-Dim  |
| Number of leds / sticks | 180      |
| Colour consistency SDCM | SDCM5    |
| Dim to warm             | No       |
| Adjustable beam angle   | No       |

| Light                       |         |
|-----------------------------|---------|
| Kelvin                      | 4000 K  |
| Colour temp nr              | 840     |
| Stable lumen                | 4000 lm |
| Color Rendering Index (CRI) | 80      |

| Ordering details |                |                |
|------------------|----------------|----------------|
| L490215840       | Quantity pc(s) | EAN            |
| Single package   | 1              | 8718739061767  |
| Outer carton     | 10             | 28718739061761 |

| Remark  |
|---|
| Can be quickly fitted as a replacement into luminaires operating on electro-magnetic control gear using the dummy starter, or on electronic gear with a simple re-wire (no dummy starter needed). |