PROFESSIONAL LIGHTING

L490215840

LED G13 Glass T8 Tube T26x1514mm including pin 230V 4000Lm 24W 4000K 840 210° AC+CCG Milky Non-Dimmable



Marine & Industry, T8 Tube AC+CCG Premium

General

Eprel registration no	831507
Socket	G13
Bulb shape	T8
Width	26.00 mm
Depth	26.00 mm
Height	1514.00 mm
Finish	Opal
Colour	White
Colour housing	White
Body material	Glass
Lifespan	50000 hours
Switches	25000
Beam angle	210 °
Dimmable	No
Degree of protection	IP20
Net weight	0.265 kg
Warranty	2 years

Energy

Operating voltage	230 V
Volt	220..240 V
Frequency	50..60 Hz
Watt	24 W
Current type	AC
Power factor	0.9
Energy efficiency class	C
Energy consumption	24 W
Lamp efficacy	166.67

LED

Filament LED	No
LED type	SMD 2835
Dimm type	Non-Dim
Number of leds / sticks	180
Colour consistency SDCM	SDCM5
Dim to warm	No
Adjustable beam angle	No

Light

CRI	80
Kelvin	4000 K
Colour temp nr	840
Stable lumen	4000 lm

Ordering details

L490215840	Quantity pc(s)	EAN
Single package	1	8718739061767
Outer carton	10	28718739061761

Remark

Can be quickly fitted as a replacement into luminaires operating on electro-magnetic control gear using the dummy starter, or AC 230V mains voltage with a simple re-wire (no dummy starter needed).

CE | UK CA

Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | www.spl-lighting.com | info@spl-lighting.com | Telephone +31 (0)76 - 503 77 17
Fax +31 (0)76 501 78 69 | splprofessionallighting | schiefersignaal