PROFESSIONAL LIGHTING

L490312865

LED G13 Glass T8 Tube T26x1213mm
including pins 2800Lm 22W 6500K 865
190° ECG Milky Non-Dimmable



Marine & Industry, T8 Tube ECG

General	
Eprel registration no	2757701
Socket	G13
Bulb shape	T8
Width	26.00 mm
Depth	26.00 mm
Height	1213.00 mm
Finish	Opal
Colour	White
Colour housing	White
Body material	Glass
Lifespan	25000 hours
Switches	50000
Beam angle	190 °
Dimmable	No
Degree of protection	IP23
Net weight	0.200 kg
Warranty	3 years

Energy	
Operating voltage	230 V
Volt	220..240 V
Frequency	50..60 Hz
Watt	22 W
Current type	AC
Power factor	0.9
Energy efficiency class	E
Energy consumption	22 W
Lamp efficacy	127.27

LED	
Filament LED	No
LED type	SMD 2835
Dimm type	Non-Dim
Number of leds / sticks	168
Colour consistency SDCM	SDCM5
Dim to warm	No
Adjustable beam angle	No

Light	
CRI	80
Kelvin	6500 K
Colour temp nr	865
Stable lumen	2800 lm

Ordering details		
L490312865	Quantity pc(s)	EAN
Single package	1	8718739083776
Outer carton	25	28718739083770

Remark
For easy replacement of conventional T8 fluorescent lamps in existing luminaires with a compatible electronic control gear. Plug-and-play installation without any wiring modifications.

CE | UK CA

Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | www.spl-lighting.com | info@spl-lighting.com | Telephone +31 (0)76 - 503 77 17
Fax +31 (0)76 501 78 69 | splprofessionallighting | schiefersignaal