PROFESSIONAL LIGHTING

## L490360830

LED G13 Glass T8 Tube T26x604mm
including pins 1150Lm 11W 3000K 830 190°
ECG Milky Non-Dimmable



### Marine & Industry, T8 Tube ECG

| General | |
|---|---|
| Eprel registration no | 2757696 |
| Socket | G13 |
| Bulb shape | T8 |
| Width | 26.00 mm |
| Depth | 26.00 mm |
| Height | 604.00 mm |
| Finish | Opal |
| Colour | White |
| Colour housing | White |
| Body material | Glass |
| Lifespan | 25000 hours |
| Switches | 50000 |
| Beam angle | 190 ° |
| Dimmable | No |
| Degree of protection | IP23 |
| Net weight | 0.099 kg |
| Warranty | 3 years |

| Energy | |
|---|---|
| Operating voltage | 230 V |
| Volt | 220..240 V |
| Frequency | 50..60 Hz |
| Watt | 11 W |
| Current type | AC |
| Power factor | 0.9 |
| Energy efficiency class | F |
| Energy consumption | 11 W |
| Lamp efficacy | 104.55 |

| LED | |
|---|---|
| Filament LED | No |
| LED type | SMD 2835 |
| Dimm type | Non-Dim |
| Number of leds / sticks | 60 |
| Colour consistency SDCM | SDCM5 |
| Dim to warm | No |
| Adjustable beam angle | No |

| Light | |
|---|---|
| CRI | 80 |
| Kelvin | 3000 K |
| Colour temp nr | 830 |
| Stable lumen | 1150 lm |

| Ordering details | | |
|---|---|---|
| L490360830 | Quantity pc(s) | EAN |
| Single package | 1 | 8718739083820 |
| Outer carton | 25 | 28718739083824 |

### Remark

For easy replacement of conventional T8 fluorescent lamps in existing luminaires with a compatible electronic control gear. Plug-and-play installation without any wiring modifications.

CE | UK CA

Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | www.spl-lighting.com | info@spl-lighting.com | Telephone +31 (0)76 - 503 77 17
Fax +31 (0)76 501 78 69 | splprofessionallighting | schiefersignaal