PROFESSIONAL LIGHTING

L490544930

LED G5 Glass T5 Tube T16x1449mm
including pins 3060Lm 26W 3000K 830
190° AC Milky Non-Dimmable



Marine & Industry, T5 Tube AC

General	
Eprel registration no	2835617
Socket	G5
Bulb shape	T5
Width	16.00 mm
Depth	16.00 mm
Height	1449.00 mm
Finish	Opal
Colour	White
Colour housing	White
Body material	Glass
Lifespan	50000 hours
Switches	50000
Beam angle	190 °
Dimmable	No
Degree of protection	IP23
Net weight	0.150 kg
Warranty	3 years

Energy	
Operating voltage	230 V
Volt	220..240 V
Frequency	50..60 Hz
Watt	26 W
Current type	AC
Power factor	0.9
Energy efficiency class	E
Energy consumption	26 W
Lamp efficacy	117.69

LED	
Filament LED	No
LED type	SMD 2835
Dimm type	Non-Dim
Number of leds / sticks	120
Colour consistency SDCM	SDCM5
Dim to warm	No
Adjustable beam angle	No

Light	
CRI	80
Kelvin	3000 K
Colour temp nr	830
Stable lumen	3060 lm

Ordering details		
L490544930	Quantity pc(s)	EAN
Single package	1	8718739083523
Outer carton	25	28718739083527

CE | UK CA

Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | www.spl-lighting.com | info@spl-lighting.com | Telephone +31 (0)76 - 503 77 17
Fax +31 (0)76 501 78 69 | splprofessionallighting | schiefersignaal