PROFESSIONAL LIGHTING

L490614965

LED G5 Glass T5 Tube T16x1162mm
including pins 2600Lm 20W 6500K 865
190° HF/ECG Milky Non-Dimmable

Marine & Industry, T5 Tube HF/ECG



General	
Eprel registration no	2757692
Socket	G5
Bulb shape	T5
Width	16.00 mm
Depth	16.00 mm
Height	1162.00 mm
Finish	Opal
Colour	White
Colour housing	White
Body material	Glass
Lifespan	50000 hours
Switches	50000
Beam angle	190 °
Dimmable	No
Degree of protection	IP23
Net weight	0.128 kg
Warranty	3 years

Energy	
Operating voltage	230 V
Volt	220..240 V
Frequency	50..60 Hz
Watt	20 W
Current type	AC
Power factor	0.9
Energy efficiency class	E
Energy consumption	20 W
Lamp efficacy	130.00

LED	
Filament LED	No
LED type	SMD 2835
Dimm type	Non-Dim
Number of leds / sticks	92
Colour consistency SDCM	SDCM5
Dim to warm	No
Adjustable beam angle	No

Light	
CRI	80
Kelvin	6500 K
Colour temp nr	865
Stable lumen	2600 lm

Ordering details		
L490614965	Quantity pc(s)	EAN
Single package	1	8718739083684
Outer carton	25	28718739083688

Remark

For easy replacement of conventional T5 fluorescent lamps in existing luminaires with a compatible electronic control gear (ECG/HF). Plug-and-play installation without any wiring modifications.

CE | UK CA

Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | www.spl-lighting.com | info@spl-lighting.com | Telephone +31 (0)76 - 503 77 17
Fax +31 (0)76 501 78 69 | splprofessionallighting | schiefersignaal