PROFESSIONAL LIGHTING

## L495810808

LED G13 Glass T8 BLB Blacklight Blue Tube
T26x1499mm excluding pins 230V 20W
360° AC+CCG 30.000 hours Non-Dimmable



### Marine & Industry, T8 BLB Tube AC+CCG

| General | |
|---|---|
| Socket | G13 |
| Bulb shape | T8 |
| Width | 26.00 mm |
| Depth | 26.00 mm |
| Height | 1499.00 mm |
| Finish | Clear |
| Colour | Purple Blacklight Blue |
| Colour housing | White |
| Body material | Glass |
| Lifespan | 30000 hours |
| Switches | 50000 |
| Beam angle | 360 ° |
| Dimmable | No |
| Degree of protection | IP20 |
| Net weight | 0.200 kg |
| Warranty | 2 years |

| Energy | |
|---|---|
| Operating voltage | 230 V |
| Volt | 185..265 V |
| Frequency | 50..60 Hz |
| Watt | 20 W |
| Current type | AC |
| Power factor | 0.5 |
| Energy consumption | 20 W |

| LED | |
|---|---|
| Filament LED | No |
| LED type | SMD 2835 |
| Dimm type | Non-Dim |
| Number of leds / sticks | 120 |
| Colour consistency SDCM | SDCM5 |
| Dim to warm | No |
| Adjustable beam angle | No |

| Ordering details | | |
|---|---|---|
| L495810808 | Quantity pc(s) | EAN |
| Single package | 1 | 8718739085510 |
| Outer carton | 25 | 28718739085514 |

| Remark |
|---|
| Can be quickly fitted as a replacement into luminaires operating on electro-magnetic control gear using the dummy starter, or AC 230V mains voltage with a simple re-wire (no dummy starter needed). |

CE | UK CA

Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | www.spl-lighting.com | info@spl-lighting.com | Telephone +31 (0)76 - 503 77 17
Fax +31 (0)76 501 78 69 | splprofessionallighting | schiefersignaal