PROFESSIONAL LIGHTING

L498150003

LED G13 Glass T8 Tube T28x1513mm including pin 230V 22W 200° AC+CCG Green Non-Dimmable

Marine & Industry, T8 Colour Tube AC+CCG



General

Socket	G13
Bulb shape	T8
Width	28.00 mm
Depth	28.00 mm
Height	1513.00 mm
Finish	Opal
Colour	Green
Colour housing	White
Body material	Glass
Lifespan	25000 hours
Switches	25000
Beam angle	200 °
Dimmable	No
Degree of protection	IP20
Net weight	0.220 kg
Warranty	2 years

Light

Stable lumen	3000 lm

Remark

Can be quickly fitted as a replacement into luminaires operating on electro-magnetic control gear using the dummy starter, or AC 230V mains voltage with a simple re-wire (no dummy starter needed).

Energy

Operating voltage	230 V
Volt	220..240 V
Frequency	50..60 Hz
Watt	22 W
Current type	AC
Power factor	0.6
Energy consumption	22 W

LED

Filament LED	No
LED type	SMD
Dimm type	Non-Dim
Number of leds / sticks	100
Colour consistency SDCM	SDCM5
Dim to warm	No
Adjustable beam angle	No

Ordering details

L498150003	Quantity pc(s)	EAN
Single package	1	8718739080881
Outer carton	25	28718739080885

CE | UK CA

Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | www.spl-lighting.com | info@spl-lighting.com | Telephone +31 (0)76 - 503 77 17
Fax +31 (0)76 501 78 69 | splprofessionallighting | schiefersignaal