




# PROFESSIONAL LIGHTING

## L550810927

LED Ba15d AR56x58mm 12V 400Lm 8W  
2700K 927 10° AC/DC Grey Dimmable L1

**Specials & Projects, Spot Ba15d AR56  
Premium**



| General                     |             | Energy                  |                           |
|-----------------------------|-------------|-------------------------|---------------------------|
| Epel registration no        | 1960809     | Operating voltage       | 12 V                      |
| Socket                      | Ba15d       | Volt                    | 10..14 V                  |
| Bulb shape                  | AR56        | Frequency               | 50..60 Hz                 |
| Width                       | 56.00 mm    | Watt                    | 8 W                       |
| Depth                       | 56.00 mm    | Current type            | AC/DC                     |
| Height                      | 58.00 mm    | Power factor            | 0.9                       |
| Finish                      | Clear       | Energy efficiency class | G                         |
| Colour                      | Silver      | Energy consumption      | 8 W                       |
| Colour housing              | Grey        | Lamp efficacy           | 50.00                     |
| Body material               | Aluminium   | LED                     |                           |
| Lifespan                    | 25000 hours | Filament LED            | No                        |
| Switches                    | 30000       | LED type                | SMD                       |
| Beam angle                  | 10 °        | Dimm type               | Trailing and leading edge |
| Dimmable                    | Yes         | Number of leds / sticks | 1                         |
| Degree of protection        | IP20        | Colour consistency SDCM | SDCM3                     |
| Net weight                  | 0.063 kg    | Dim to warm             | No                        |
| Warranty                    | 3 years     | Adjustable beam angle   | No                        |
| Light                       |             | Ordering details        |                           |
| Kelvin                      | 2700 K      | L550810927              | Quantity pc(s) EAN        |
| Colour temp nr              | 927         | Single package          | 1 8718739072237           |
| Stable lumen                | 480 lm      | Inner carton            | 10 18718739072234         |
| Lumen 90 cone               | 400 lm      | Outer carton            | 50 28718739072231         |
| Luminous intensity          | 2900 cd     |                         |                           |
| Color Rendering Index (CRI) | 92          |                         |                           |



Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | [www.spl-lighting.com](http://www.spl-lighting.com) | [info@spl-lighting.com](mailto:info@spl-lighting.com) | Telephone +31 (0)76 - 503 77 17  
Fax +31 (0)76 501 78 69 | [f splprofessionalighting](#) | [s schiefersignaal](#)



23-12-2024