



PROFESSIONAL
LIGHTING

L560835900

LED Ba15d DimToWarm AR70x55mm 12V
330Lm 8W 2000-2800K 920-928 35°
AC/DC Grey Dimmable

**Specials & Projects, Spot Ba15d AR70
Premium**



General		Energy															
Eprel registration no	831518	Operating voltage	12 V														
Socket	Ba15d	Volt	12 V														
Bulb shape	AR70	Frequency	50..60 Hz														
Width	70.00 mm	Watt	8 W														
Depth	70.00 mm	Current type	AC/DC														
Height	55.00 mm	Power factor	0.9														
Finish	Clear	Energy efficiency class	G														
Colour	Silver	Energy consumption	8 W														
Colour housing	Grey	Lamp efficacy	41.25														
Body material	Aluminium	<div>LED</div> <table><tr><td>Filament LED</td><td>No</td></tr><tr><td>LED type</td><td>SMD</td></tr><tr><td>Dimm type</td><td>Trailing and leading edge</td></tr><tr><td>Number of leds / sticks</td><td>1</td></tr><tr><td>Colour consistency SDCM</td><td>SDCM3</td></tr><tr><td>Dim to warm</td><td>Yes</td></tr><tr><td>Adjustable beam angle</td><td>No</td></tr></table>		Filament LED	No	LED type	SMD	Dimm type	Trailing and leading edge	Number of leds / sticks	1	Colour consistency SDCM	SDCM3	Dim to warm	Yes	Adjustable beam angle	No
Filament LED	No																
LED type	SMD																
Dimm type	Trailing and leading edge																
Number of leds / sticks	1																
Colour consistency SDCM	SDCM3																
Dim to warm	Yes																
Adjustable beam angle	No																
Lifespan	25000 hours																
Switches	30000																
Beam angle	35 °																
Dimmable	Yes																
Degree of protection	IP20																
Net weight	0.043 kg																
Warranty	3 years																

Light		Ordering details		
Kelvin	2000..2800 K	L560835900	Quantity pc(s)	EAN
Colour temp nr	920..928	Single package	1	8718739061521
Stable lumen	440 lm	Inner carton	10	18718739061528
Lumen 90 cone	330 lm	Outer carton	50	28718739061525
Luminous intensity	1100 cd			
Color Rendering Index (CRI)	95			

Remark

For Dali systems, please contact our sales department. Is available on request



Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | www.spl-lighting.com | info@spl-lighting.com | Telephone +31 (0)76 - 503 77 17
Fax +31 (0)76 501 78 69 | [f splprofessionalighting](#) | [schiefersignaal](#)

22-11-2024