PROFESSIONAL LIGHTING

## L571224927

LED G53 AR111x67mm 12V 650Lm 12W
2700K 927 24° AC/DC Grey Dimmable

**Specials & Projects, Spot G53 AR111 Dimmable Premium**





| General | |
|---|---|
| Eprel registration no | 831528 |
| Socket | G53 |
| Bulb shape | AR111 |
| Width | 111.00 mm |
| Depth | 111.00 mm |
| Height | 67.00 mm |
| Finish | Clear |
| Colour | Silver |
| Colour housing | Grey |
| Body material | Aluminium |
| Lifespan | 25000 hours |
| Switches | 30000 |
| Beam angle | 24 ° |
| Dimmable | Yes |
| Degree of protection | IP20 |
| Net weight | 0.095 kg |
| Warranty | 3 years |

| Energy | |
|---|---|
| Operating voltage | 12 V |
| Volt | 10..14 V |
| Frequency | 50..60 Hz |
| Watt | 12 W |
| Current type | AC/DC |
| Power factor | 0.9 |
| Energy efficiency class | G |
| Energy consumption | 12 W |
| Lamp efficacy | 54.17 |

| LED | |
|---|---|
| Filament LED | No |
| LED type | COB |
| Dimm type | Trailing and leading edge |
| Number of leds / sticks | 1 |
| Colour consistency SDCM | SDCM3 |
| Dim to warm | No |
| Adjustable beam angle | No |

| Light | |
|---|---|
| CRI | 92 |
| Kelvin | 2700 K |
| Colour temp nr | 927 |
| Stable lumen | 690 lm |
| Lumen 90 cone | 650 lm |
| Luminous intensity | 4900 cd |

| Ordering details | | |
|---|---|---|
| L571224927 | Quantity pc(s) | EAN |
| Single package | 1 | 8718739063570 |
| Inner carton | 10 | 18718739063577 |
| Outer carton | 50 | 28718739063574 |

**Remark**

Operating temperature: -20° - + 40° - Storage temperature: -20° - + 70° fully closed fixtures will seriously shorten the life

Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | www.spl-lighting.com | info@spl-lighting.com | Telephone +31 (0)76 - 503 77 17
Fax +31 (0)76 501 78 69 | splprofessionallighting | schiefersignaal