PROFESSIONAL LIGHTING

## L641036900

LED GU10 DimToWarm ES111 111x74mm
230V 730Lm 10W 2100-3000K 921-930
CRI97 36° AC Dimmable

**Specials & Projects, Spot GU10 ES111 DTW Premium**





| General | |
|---|---|
| Eprel registration no | 2342077 |
| Socket | GU10 |
| Bulb shape | ES111 |
| Width | 111.00 mm |
| Depth | 111.00 mm |
| Height | 74.00 mm |
| Finish | Clear |
| Colour | Silver |
| Colour housing | Grey |
| Body material | Aluminium |
| Lifespan | 50000 hours |
| Switches | 100000 |
| Beam angle | 36 ° |
| Dimmable | Yes |
| Degree of protection | IP20 |
| Net weight | 0.240 kg |
| Warranty | 3 years |

| Energy | |
|---|---|
| Operating voltage | 230 V |
| Volt | 220..240 V |
| Frequency | 50..60 Hz |
| Watt | 10 W |
| Current type | AC |
| Power factor | 0.9 |
| Energy efficiency class | F |
| Energy consumption | 10 W |
| Lamp efficacy | 73.00 |

| LED | |
|---|---|
| Filament LED | No |
| LED type | COB |
| Dimm type | Trailing and leading edge |
| Number of leds / sticks | 1 |
| Colour consistency SDCM | SDCM3 |
| Dim to warm | Yes |
| Adjustable beam angle | No |

| Light | |
|---|---|
| CRI | 97 |
| Kelvin | 2100..3000 K |
| Colour temp nr | 921..930 |
| Stable lumen | 810 lm |
| Lumen 90 cone | 730 lm |
| Luminous intensity | 2000 cd |

| Ordering details | | |
|---|---|---|
| L641036900 | Quantity pc(s) | EAN |
| Single package | 1 | 8718739082267 |
| Outer carton | 24 | 28718739082261 |

Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | www.spl-lighting.com | info@spl-lighting.com | Telephone +31 (0)76 - 503 77 17
Fax +31 (0)76 501 78 69 | splprofessionallighting | schiefersignaal