PROFESSIONAL LIGHTING

L641801230

LED R7s T29x118mm 230V 1520Lm 12.5W
3000K 830 360° AC Clear Dimmable
Aluminum

Household, R7s





General	
Eprel registration no	860471
Socket	R7s
Bulb shape	T29
Width	29.00 mm
Depth	29.00 mm
Height	118.00 mm
Finish	Clear
Colour	Colourless
Body material	Polycarbonat
Lifespan	15000 hours
Switches	50000
Beam angle	360 °
Dimmable	Yes
Degree of protection	IP20
Net weight	0.073 kg
Warranty	2 years

Light	
CRI	80
Kelvin	3000 K
Colour temp nr	830
Stable lumen	1520 lm

Energy	
Operating voltage	230 V
Volt	220..240 V
Frequency	50..60 Hz
Watt	12.5 W
Current type	AC
Power factor	0.9
Energy efficiency class	F
Energy consumption	13 W
Lamp efficacy	121.60

LED	
Filament LED	No
LED type	SMD 2835
Dimm type	Triac
Number of leds / sticks	96
Colour consistency SDCM	SDCM6
Dim to warm	No
Adjustable beam angle	No

Ordering details

L641801230	Quantity pc(s)	EAN
Single package	1	8718739065772
Inner carton	10	18718739065779
Outer carton	100	28718739065776

CE | UK CA

Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | www.spl-lighting.com | info@spl-lighting.com | Telephone +31 (0)76 - 503 77 17
Fax +31 (0)76 501 78 69 | splprofessionallighting | schiefersignaal