PROFESSIONAL LIGHTING

L641824530

LED R7s T26x118mm 20-50V 1250Lm 9.5W 3000K 830 360° AC/DC Clear Non-Dimmable

Marine & Industry, R7s 20-50V Premium





General	
Eprel registration no	2833824
Socket	R7s
Bulb shape	T26
Width	26.00 mm
Depth	26.00 mm
Height	118.00 mm
Finish	Clear
Colour	Colourless
Colour housing	Colourless
Body material	Ceramic
Lifespan	25000 hours
Switches	50000
Beam angle	360 °
Dimmable	No
Degree of protection	IP20
Net weight	0.035 kg
Warranty	3 years

Energy	
Operating voltage	24 V
Volt	20..50 V
Frequency	60 Hz
Watt	9.5 W
Current type	AC/DC
Power factor	0.6
Energy efficiency class	E
Energy consumption	10 W
Lamp efficacy	131.58

LED	
Filament LED	No
LED type	SMD 2835
Dimm type	Non-Dim
Number of leds / sticks	84
Colour consistency SDCM	SDCM6
Dim to warm	No
Adjustable beam angle	No

Light	
CRI	80
Kelvin	3000 K
Colour temp nr	830
Stable lumen	1250 lm

Ordering details		
L641824530	Quantity pc(s)	EAN
Single package	1	8718739085572
Inner carton	10	18718739085579
Outer carton	100	28718739085576

CE | UK CA

Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | www.spl-lighting.com | info@spl-lighting.com | Telephone +31 (0)76 - 503 77 17
Fax +31 (0)76 501 78 69 | splprofessionallighting | schiefersignaal