



L642731027

LED GU5.3 MR16 50x50mm 12V 280Lm 3W
2700K 827 12° AC/DC Dimmable

Household, Spot GU5.3 12V



| General | | Energy | | |
|-----------------------------|--------------|-------------------------|----------------|----------------|
| Eprel registration no | 2179436 | Operating voltage | 12 V | |
| Socket | GU5.3 | Volt | 11..13 V | |
| Bulb shape | MR16 | Frequency | 50..60 Hz | |
| Width | 50.00 mm | Watt | 3 W | |
| Depth | 50.00 mm | Current type | AC/DC | |
| Height | 50.00 mm | Power factor | 0.6 | |
| Finish | Clear | Energy efficiency class | F | |
| Colour | Colourless | Energy consumption | 3 W | |
| Colour housing | Silver | Lamp efficacy | 93.33 | |
| Body material | Polycarbonat | LED | | |
| Lifespan | 25000 hours | Filament LED | No | |
| Switches | 50000 | LED type | SMD | |
| Beam angle | 12 ° | Dimm type | Triac | |
| Dimmable | Yes | Number of leds / sticks | 1 | |
| Degree of protection | IP20 | Colour consistency SDCM | SDCM6 | |
| Net weight | 0.020 kg | Dim to warm | No | |
| Warranty | 2 years | Adjustable beam angle | No | |
| Light | | Ordering details | | |
| Kelvin | 2700 K | L642731027 | Quantity pc(s) | EAN |
| Colour temp nr | 827 | Single package | 1 | 8718739077379 |
| Stable lumen | 300 lm | Inner carton | 10 | 18718739077376 |
| Lumen 90 cone | 280 lm | Outer carton | 100 | 28718739077373 |
| Lumen 120 cone | 290 lm | | | |
| Luminous intensity | 2862 cd | | | |
| Color Rendering Index (CRI) | 80 | | | |

