



L642742630

LED GU5.3 MR16 50x48mm 24-30V 425Lm
6W 3000K 830 38° DC Non-Dimmable

Marine & Industry, Spot GU5.3 24V Premium



| General | | Energy | | |
|-----------------------------|--------------|-------------------------|----------------|----------------|
| Eprel registration no | 831583 | Volt | 24..30 V | |
| Socket | GU5.3 | Frequency | 50 Hz | |
| Bulb shape | MR16 | Watt | 6 W | |
| Width | 50.00 mm | Current type | DC | |
| Depth | 50.00 mm | Power factor | 1 | |
| Height | 48.00 mm | Energy efficiency class | G | |
| Finish | Clear | Energy consumption | 6 W | |
| Colour | Colourless | Lamp efficacy | 70.83 | |
| Colour housing | White | LED | | |
| Body material | Polycarbonat | Filament LED | No | |
| Lifespan | 15000 hours | LED type | SMD 2835 | |
| Switches | 50000 | Dimm type | Non-Dim | |
| Beam angle | 38 ° | Number of leds / sticks | 8 | |
| Dimmable | No | Colour consistency SDCM | SDCM5 | |
| Degree of protection | IP20 | Dim to warm | No | |
| Net weight | 0.026 kg | Adjustable beam angle | No | |
| Warranty | 3 years | Ordering details | | |
| Light | | L642742630 | Quantity pc(s) | EAN |
| Kelvin | 3000 K | Single package | 1 | 8718739057579 |
| Colour temp nr | 830 | Inner carton | 10 | 18718739057576 |
| Stable lumen | 475 lm | Outer carton | 100 | 28718739057573 |
| Lumen 90 cone | 425 lm | | | |
| Luminous intensity | 650 cd | | | |
| Color Rendering Index (CRI) | 82 | | | |

