



L642767527

LED GU10 MR16 50x55mm 230V 675Lm
6W 2700K 827 36° AC Dimmable

Marine & Industry, Spot GU10 Dimmable



| General | | Energy | |
|-----------------------|-------------|-------------------------|------------|
| Eprel registration no | 2037907 | Operating voltage | 230 V |
| Socket | GU10 | Volt | 220..240 V |
| Bulb shape | MR16 | Frequency | 50..60 Hz |
| Width | 50.00 mm | Watt | 6 W |
| Depth | 50.00 mm | Current type | AC |
| Height | 55.00 mm | Power factor | 0.9 |
| Finish | Clear | Energy efficiency class | E |
| Colour | Colourless | Energy consumption | 6 W |
| Colour housing | White | Lamp efficacy | 112.50 |
| Body material | PVC | LED | |
| Lifespan | 25000 hours | Filament LED | No |
| Switches | 30000 | LED type | SMD 2835 |
| Beam angle | 36 ° | Dimm type | Triac |
| Dimmable | Yes | Number of leds / sticks | 14 |
| Degree of protection | IP20 | Colour consistency SDCM | SDCM6 |
| Net weight | 0.034 kg | Dim to warm | No |
| Warranty | 2 years | Adjustable beam angle | No |

| Light | |
|-----------------------------|---------|
| Kelvin | 2700 K |
| Colour temp nr | 827 |
| Stable lumen | 750 lm |
| Lumen 90 cone | 675 lm |
| Luminous intensity | 1194 cd |
| Color Rendering Index (CRI) | 80 |

| Ordering details | | |
|------------------|----------------|----------------|
| L642767527 | Quantity pc(s) | EAN |
| Single package | 1 | 8718739075931 |
| Inner carton | 10 | 18718739075938 |
| Outer carton | 100 | 28718739075935 |

Remark
General note: GU10 glass versions need to cool down after 8 hrs burning (switch off for half an hour), because of limited heat dissipation

