



L643090040

LED GU10 Glass T30x80mm 230V 440Lm
4W 4000K 840 AC Non-Dimmable

Household, GU10 Tubular



| General | | Energy | | |
|-----------------------------|-------------|-------------------------|----------------|----------------|
| Eprel registration no | 695079 | Operating voltage | 230 V | |
| Socket | GU10 | Volt | 220..240 V | |
| Bulb shape | T30 | Frequency | 50..60 Hz | |
| Width | 30.00 mm | Watt | 4 W | |
| Depth | 30.00 mm | Current type | AC | |
| Height | 80.00 mm | Power factor | 0.5 | |
| Finish | Clear | Energy efficiency class | E | |
| Colour | Colourless | Energy consumption | 4 W | |
| Colour housing | White | Lamp efficacy | 110.00 | |
| Body material | Glass | LED | | |
| Lifespan | 20000 hours | Filament LED | No | |
| Switches | 10000 | LED type | SMD | |
| Beam angle | 300 ° | Dimm type | Non-Dim | |
| Dimmable | No | Number of leds / sticks | 34 | |
| Degree of protection | IP20 | Colour consistency SDCM | SDCM5 | |
| Net weight | 0.027 kg | Dim to warm | No | |
| Warranty | 2 years | Adjustable beam angle | No | |
| Light | | Ordering details | | |
| Kelvin | 4000 K | L643090040 | Quantity pc(s) | EAN |
| Colour temp nr | 840 | Single package | 1 | 8718739064997 |
| Stable lumen | 440 lm | Inner carton | 10 | 18718739064994 |
| Color Rendering Index (CRI) | 80 | Outer carton | 200 | 28718739064991 |

