PROFESSIONAL LIGHTING

## L643090040

LED GU10 Glass T30x80mm 230V 440Lm
4W 4000K 840 AC Non-Dimmable

**Household, GU10 Tubular**





| General | |
|---|---|
| Eprel registration no | 695079 |
| Socket | GU10 |
| Bulb shape | T30 |
| Width | 30.00 mm |
| Depth | 30.00 mm |
| Height | 80.00 mm |
| Finish | Clear |
| Colour | Colourless |
| Colour housing | White |
| Body material | Glass |
| Lifespan | 20000 hours |
| Switches | 10000 |
| Beam angle | 300 ° |
| Dimmable | No |
| Degree of protection | IP20 |
| Net weight | 0.027 kg |
| Warranty | 2 years |

| Energy | |
|---|---|
| Operating voltage | 230 V |
| Volt | 220..240 V |
| Frequency | 50..60 Hz |
| Watt | 4 W |
| Current type | AC |
| Power factor | 0.5 |
| Energy efficiency class | E |
| Energy consumption | 4 W |
| Lamp efficacy | 110.00 |

| LED | |
|---|---|
| Filament LED | No |
| LED type | SMD |
| Dimm type | Non-Dim |
| Number of leds / sticks | 34 |
| Colour consistency SDCM | SDCM5 |
| Dim to warm | No |
| Adjustable beam angle | No |

| Light | |
|---|---|
| CRI | 80 |
| Kelvin | 4000 K |
| Colour temp nr | 840 |
| Stable lumen | 440 lm |

| Ordering details | | |
|---|---|---|
| L643090040 | Quantity pc(s) | EAN |
| Single package | 1 | 8718739064997 |
| Inner carton | 10 | 18718739064994 |
| Outer carton | 200 | 28718739064991 |

CE | UK CA

Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | www.spl-lighting.com | info@spl-lighting.com | Telephone +31 (0)76 - 503 77 17
Fax +31 (0)76 501 78 69 | splprofessionallighting | schiefersignaal