

L643090040

LED GU10 Glass 30x80mm 230V 440Lm
4W 4000K 840 AC Non-Dimmable

Household, GU10 Glass



General		Energy																							
Eprel registration no	695079	Operating voltage		230 V																					
Socket	GU10	Volt		220..240 V																					
Bulb shape	T30	Frequency		50..60 Hz																					
Width	30.00 mm	Watt		4 W																					
Depth	30.00 mm	Current type		AC																					
Height	80.00 mm	Power factor		0.5																					
Finish	Clear	Energy efficiency class		E																					
Colour	Colourless	Energy consumption		4 W																					
Colour housing	White	Replacement wattage		38 W																					
Body material	Glass	Lamp efficacy		110.00																					
Lifespan	20000 hours	<div>LED</div> <table><tr><td colspan="2">Filament LED</td><td>No</td></tr><tr><td colspan="2">LED type</td><td>SMD</td></tr><tr><td colspan="2">Dimm type</td><td>Non-Dim</td></tr><tr><td colspan="2">Number of leds / sticks</td><td>34</td></tr><tr><td colspan="2">Colour consistency SDCM</td><td>SDCM5</td></tr><tr><td colspan="2">Dim to warm</td><td>No</td></tr><tr><td colspan="2">Adjustable beam angle</td><td>No</td></tr></table>			Filament LED		No	LED type		SMD	Dimm type		Non-Dim	Number of leds / sticks		34	Colour consistency SDCM		SDCM5	Dim to warm		No	Adjustable beam angle		No
Filament LED					No																				
LED type					SMD																				
Dimm type					Non-Dim																				
Number of leds / sticks					34																				
Colour consistency SDCM					SDCM5																				
Dim to warm					No																				
Adjustable beam angle					No																				
Switches	10000																								
Beam angle	300 °																								
Dimmable	No																								
Degree of protection	IP20																								
Net weight	0.027 kg																								
Warranty	2 years																								
Light		Ordering details																							
Kelvin	4000 K	L643090040	Quantity pc(s)	EAN																					
Colour temp nr	840	Single package	1	8718739064997																					
Stable lumen	440 lm	Inner carton	10	18718739064994																					
Color Rendering Index (CRI)	80	Outer carton	200	28718739064991																					