



L649950027

LED Module 50x26mm 230V 480Lm 5W
2700K 827 38° AC White Dimmable with
20cm wire and wire box

Household, Module Spot



| General | | Energy | |
|-----------------------------|--------------|-------------------------|--------------------|
| Eprel registration no | 1427452 | Operating voltage | 230 V |
| Socket | Wire Ended | Volt | 220..240 V |
| Bulb shape | MR16 | Frequency | 50..60 Hz |
| Width | 50.00 mm | Watt | 5 W |
| Depth | 50.00 mm | Current type | AC |
| Height | 26.00 mm | Power factor | 0.5 |
| Finish | Clear | Energy efficiency class | E |
| Colour | Colourless | Energy consumption | 5 W |
| Colour housing | White | Lamp efficacy | 99.60 |
| Body material | Polycarbonat | LED | |
| Lifespan | 25000 hours | Filament LED | No |
| Switches | 15000 | LED type | SMD |
| Beam angle | 38 ° | Dimm type | Triac |
| Dimmable | Yes | Number of leds / sticks | 8 |
| Degree of protection | IP20 | Colour consistency SDCM | SDCM6 |
| Net weight | 0.052 kg | Dim to warm | No |
| Warranty | 2 years | Adjustable beam angle | No |
| Light | | Ordering details | |
| Kelvin | 2700 K | L649950027 | Quantity pc(s) EAN |
| Colour temp nr | 827 | Single package | 1 8718739068940 |
| Stable lumen | 498 lm | Inner carton | 10 18718739068947 |
| Lumen 90 cone | 480 lm | Outer carton | 100 28718739068944 |
| Luminous intensity | 961 cd | | |
| Color Rendering Index (CRI) | 80 | | |

