



L658928435

LED 2D GR10q 4pin 200x200mm 230V 14W
1680Lm 835 130° 3500K (repl. 2D 28W)
Opal AC Non-Dimmable

Marine & Industry, Led 2D



| General | |
|-----------------------|--------------|
| Eprel registration no | 2271199 |
| Socket | GR10q |
| Width | 200.00 mm |
| Depth | 30.00 mm |
| Height | 200.00 mm |
| Finish | Opal |
| Colour | White |
| Colour housing | White |
| Body material | Polycarbonat |
| Lifespan | 15000 hours |
| Switches | 15000 |
| Beam angle | 130 ° |
| Dimmable | No |
| Degree of protection | IP20 |
| Net weight | 0.120 kg |
| Warranty | 2 years |

| Energy | |
|-------------------------|------------|
| Operating voltage | 230 V |
| Volt | 220..240 V |
| Frequency | 50..60 Hz |
| Watt | 14 W |
| Current type | AC |
| Power factor | 0.9 |
| Energy efficiency class | E |
| Energy consumption | 14 W |
| Replacement wattage | 109 W |
| Lamp efficacy | 120.00 |

| LED | |
|-------------------------|---------|
| Filament LED | No |
| LED type | SMD |
| Dimm type | Non-Dim |
| Number of leds / sticks | 60 |
| Colour consistency SDCM | SDCM6 |
| Dim to warm | No |
| Adjustable beam angle | No |

| Light | |
|-----------------------------|---------|
| Kelvin | 3500 K |
| Colour temp nr | 835 |
| Stable lumen | 1680 lm |
| Color Rendering Index (CRI) | 80 |

| Ordering details | | |
|------------------|----------------|----------------|
| L658928435 | Quantity pc(s) | EAN |
| Single package | 1 | 8718739075139 |
| Outer carton | 10 | 28718739075133 |

