



PROFESSIONAL
LIGHTING

L662006005

LED E27 Filament Flex Magnetic P215x165
230V 120Lm 4W 1800K 818 360° AC Gold
Dimmable

Decorative, Big Flex Magnetic Premium



General		Energy																			
Socket	E27	Operating voltage	230 V																		
Width	215.00 mm	Volt	220..240 V																		
Depth	215.00 mm	Frequency	50..60 Hz																		
Height	165.00 mm	Watt	4 W																		
Finish	Clear	Current type	AC																		
Colour	Gold	Power factor	0.5																		
Body material	Glass	Energy consumption	4 W																		
Lifespan	15000 hours	<div>LED</div> <table><tr><td>Filament LED</td><td>Yes</td></tr><tr><td>LED type</td><td>Flex</td></tr><tr><td>Dimm type</td><td>Triac</td></tr><tr><td>Number of leds / sticks</td><td>1</td></tr><tr><td>Stick length</td><td>300 mm</td></tr><tr><td>Stick mounting</td><td>Vertical</td></tr><tr><td>Colour consistency SDCM</td><td>SDCM5</td></tr><tr><td>Dim to warm</td><td>No</td></tr><tr><td>Adjustable beam angle</td><td>No</td></tr></table>		Filament LED	Yes	LED type	Flex	Dimm type	Triac	Number of leds / sticks	1	Stick length	300 mm	Stick mounting	Vertical	Colour consistency SDCM	SDCM5	Dim to warm	No	Adjustable beam angle	No
Filament LED	Yes																				
LED type	Flex																				
Dimm type	Triac																				
Number of leds / sticks	1																				
Stick length	300 mm																				
Stick mounting	Vertical																				
Colour consistency SDCM	SDCM5																				
Dim to warm	No																				
Adjustable beam angle	No																				
Switches	50000																				
Beam angle	360 °																				
Dimmable	Yes																				
Degree of protection	IP20																				
Net weight	0.240 kg																				
Warranty	2 years																				
Light		Ordering details																			
Kelvin	1800 K	L662006005	Quantity pc(s) EAN																		
Colour temp nr	818	Single package	1 8718739075788																		
Stable lumen	120 lm	Outer carton	4 28718739075782																		
Color Rendering Index (CRI)	80																				



Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | www.spl-lighting.com | info@spl-lighting.com | Telephone +31 (0)76 - 503 77 17
Fax +31 (0)76 501 78 69 | [f splprofessionalighting](#) | [schiefersignaal](#)

18-07-2025