



LB276081965-1

LED E27 GLS A60x110mm 100-240V
900Lm 9.5W 6500K 865 220° AC/DC Opal
Non-Dimmable

Marine & Industry, General VR
100-240V High Kelvin



| General | | Energy | | | | | | | | | | | | | | | |
|-----------------------------|----------------|---|------------|---------------|----------------|----------|----------------|-----------|---------------|-------------------------|----|-------------------------|--------------|-------------|----------------|-----------------------|----|
| Eprel registration no | 1054880 | Volt | 100..240 V | | | | | | | | | | | | | | |
| Socket | E27 | Frequency | 50..60 Hz | | | | | | | | | | | | | | |
| Bulb shape | A60 | Watt | 9.5 W | | | | | | | | | | | | | | |
| Width | 60.00 mm | Current type | AC/DC | | | | | | | | | | | | | | |
| Depth | 60.00 mm | Power factor | 0.5 | | | | | | | | | | | | | | |
| Height | 110.00 mm | Energy efficiency class | F | | | | | | | | | | | | | | |
| Finish | Opal | Energy consumption | 10 W | | | | | | | | | | | | | | |
| Colour | Colourless | Replacement wattage | 66 W | | | | | | | | | | | | | | |
| Body material | Polycarbonat | Lamp efficacy | 94.74 | | | | | | | | | | | | | | |
| Lifespan | 15000 hours | <div>LED</div> <table><tr><td>Filament LED</td><td>No</td></tr><tr><td>LED type</td><td>SMD</td></tr><tr><td>Dimm type</td><td>Non-Dim</td></tr><tr><td>Number of leds / sticks</td><td>11</td></tr><tr><td>Colour consistency SDCM</td><td>SDCM6</td></tr><tr><td>Dim to warm</td><td>No</td></tr><tr><td>Adjustable beam angle</td><td>No</td></tr></table> | | Filament LED | No | LED type | SMD | Dimm type | Non-Dim | Number of leds / sticks | 11 | Colour consistency SDCM | SDCM6 | Dim to warm | No | Adjustable beam angle | No |
| Filament LED | No | | | | | | | | | | | | | | | | |
| LED type | SMD | | | | | | | | | | | | | | | | |
| Dimm type | Non-Dim | | | | | | | | | | | | | | | | |
| Number of leds / sticks | 11 | | | | | | | | | | | | | | | | |
| Colour consistency SDCM | SDCM6 | | | | | | | | | | | | | | | | |
| Dim to warm | No | | | | | | | | | | | | | | | | |
| Adjustable beam angle | No | | | | | | | | | | | | | | | | |
| Switches | 50000 | | | | | | | | | | | | | | | | |
| Beam angle | 220 ° | | | | | | | | | | | | | | | | |
| Dimmable | No | | | | | | | | | | | | | | | | |
| Degree of protection | IP20 | | | | | | | | | | | | | | | | |
| Net weight | 0.020 kg | | | | | | | | | | | | | | | | |
| Warranty | 2 years | | | | | | | | | | | | | | | | |
| Light | | <div>Ordering details</div> <table><tr><td>LB276081965-1</td><td>Quantity pc(s)</td><td>EAN</td></tr><tr><td>Single package</td><td>1</td><td>8718739066137</td></tr><tr><td>Inner carton</td><td>10</td><td>18718739066134</td></tr><tr><td>Outer carton</td><td>50</td><td>28718739066131</td></tr></table> | | LB276081965-1 | Quantity pc(s) | EAN | Single package | 1 | 8718739066137 | Inner carton | 10 | 18718739066134 | Outer carton | 50 | 28718739066131 | | |
| LB276081965-1 | Quantity pc(s) | EAN | | | | | | | | | | | | | | | |
| Single package | 1 | 8718739066137 | | | | | | | | | | | | | | | |
| Inner carton | 10 | 18718739066134 | | | | | | | | | | | | | | | |
| Outer carton | 50 | 28718739066131 | | | | | | | | | | | | | | | |
| Kelvin | 6500 K | | | | | | | | | | | | | | | | |
| Colour temp nr | 865 | | | | | | | | | | | | | | | | |
| Stable lumen | 900 lm | | | | | | | | | | | | | | | | |
| Color Rendering Index (CRI) | 80 | | | | | | | | | | | | | | | | |