PROFESSIONAL LIGHTING

LE480105540

LED PLL 2G11 4 pin Glass T43x537mm 25W
2750Lm 840 4000K (repl. PLL55W) Opal
ECG Non-Dimmable

Marine & Industry, PLL 2G11 4pin ECG

General	
Eprel registration no	2757682
Socket	2G11
Bulb shape	T43
Width	43.00 mm
Depth	23.00 mm
Height	537.00 mm
Finish	Opal
Colour	White
Colour housing	White
Body material	Glass
Lifespan	25000 hours
Switches	15000
Beam angle	270 °
Dimmable	No
Degree of protection	IP20
Net weight	0.153 kg
Warranty	2 years

Energy	
Operating voltage	230 V
Volt	220..240 V
Frequency	50..60 Hz
Watt	25 W
Current type	AC
Power factor	0.7
Energy efficiency class	E
Energy consumption	25 W
Lamp efficacy	110.00

LED	
Filament LED	No
LED type	SMD 2835
Dimm type	Non-Dim
Number of leds / sticks	120
Colour consistency SDCM	SDCM6
Dim to warm	No
Adjustable beam angle	No

Light	
CRI	80
Kelvin	4000 K
Colour temp nr	840
Stable lumen	2750 lm

Ordering details		
LE480105540	Quantity pc(s)	EAN
Single package	1	8718739075733
Inner carton	10	18718739075730
Outer carton	50	28718739075737

Remark
For easy replacement of conventional PL lamps in existing luminaires with a compatible electronic control gear. Plug-and-play installation without any wiring modifications.

CE | UK CA

Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | www.spl-lighting.com | info@spl-lighting.com | Telephone +31 (0)76 - 503 77 17
Fax +31 (0)76 501 78 69 | splprofessionallighting | schiefersignaal