PROFESSIONAL LIGHTING

LE480502640

LED PLC G24q-3 4 pin Glass T34x163mm
10W 1100Lm 840 4000K (repl. PLDE26W)
Opal ECG Non-Dimmable

Marine & Industry, PLC G24q 4pin ECG



General	
Eprel registration no	2757670
Socket	G24q-3
Bulb shape	T34
Width	34.00 mm
Depth	35.00 mm
Height	163.00 mm
Finish	Opal
Colour	White
Colour housing	White
Body material	Glass
Lifespan	25000 hours
Switches	15000
Beam angle	360 °
Dimmable	No
Degree of protection	IP20
Net weight	0.070 kg
Warranty	2 years

Energy	
Operating voltage	230 V
Volt	220..240 V
Frequency	50..60 Hz
Watt	10 W
Current type	AC
Power factor	0.9
Energy efficiency class	E
Energy consumption	10 W
Lamp efficacy	110.00

LED	
Filament LED	No
LED type	SMD 2835
Dimm type	Non-Dim
Number of leds / sticks	72
Colour consistency SDCM	SDCM6
Dim to warm	No
Adjustable beam angle	No

Light	
CRI	80
Kelvin	4000 K
Colour temp nr	840
Stable lumen	1100 lm

Ordering details		
LE480502640	Quantity pc(s)	EAN
Single package	1	8718739075665
Inner carton	10	18718739075662
Outer carton	50	28718739075669

Remark

For easy replacement of conventional PL lamps in existing luminaires with a compatible electronic control gear. Plug-and-play installation without any wiring modifications.

CE | UK CA

Pottenbakkerstraat 35, 4871 EP Etten-Leur, The Netherlands | www.spl-lighting.com | info@spl-lighting.com | Telephone +31 (0)76 - 503 77 17
Fax +31 (0)76 501 78 69 | splprofessionallighting | schiefersignaal